



Product Safety Data Sheet

Document Code: 31056

Version: 7.0

Description: BRASSO METAL POLISH

Status: Published

Revision Reason: New FG code

Issue Date: 20 May 2010

PSDS

PSDS

PAGE 1 OF TOTAL 6

1. PRODUCT and COMPANY IDENTIFICATION

Product Name Brasso Metal Polish

Other Names None

Product Code(s) 029378 (12x250mL)
0255015 (6x250mL)
0281374 (6x250mL)

Recommended Use Metal cleaner and polish.

Supplier

AUSTRALIA

COMPANY: Reckitt Benckiser (Australia) Pty Limited

ABN: 17 003 274 655

ADDRESS: 44 Wharf Road
West Ryde NSW 2114

TELEPHONE: (02) 9857 2000

AFTER HOURS EMERGENCY TELEPHONE

(5pm to 8am EST Australia): (02) 9857 2444

NEW ZEALAND

COMPANY: Reckitt Benckiser (New Zealand) Limited

ADDRESS: Lincoln Manor
289 Lincoln Road
Henderson Auckland 1231

TELEPHONE: (09) 839 0200

Poisons Centre Information

AUSTRALIA 13 1126

NEW ZEALAND 0800 764 766 or 0800 POISON

2. HAZARD(S) IDENTIFICATION

HAZARDOUS ACCORDING TO NOHSC CRITERIA
DANGEROUS GOODS ACCORDING TO ADG CODE (See Section 14)

RISK PHRASE(S)
(See Section 15) R10 Flammable
R67 Vapours may cause drowsiness and dizziness
R51/53 Toxic to aquatic organisms, may cause long term effects in the aquatic environment.

SAFETY PHRASE(S) S2 Keep out of reach of children.
S24 Avoid contact with skin
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29 Do not empty into drains.
S61 Avoid release into the environment.
S62 If swallowed, do not induce vomiting, seek medical advice immediately and show this container or label.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Proportion (%w/w)
White spirit	64742-82-1	> 60
Ammonium hydroxide	1336-21-6	< 5
Other ingredients classified as not hazardous according to NOHSC		to 100

4. FIRST AID MEASURES

Eye Contact	Wash eyes with a large amount of water. If irritation occurs and persists contact a doctor.
Skin Contact	Wash skin with warm water and soap. If irritation occurs and persists contact a doctor.
Inhalation	Remove patient to fresh air. If breathing difficulties are experienced, seek medical attention.
Ingestion	Do not induce vomiting. Contact a doctor or a Poisons Information Centre.
Advice to Doctor:	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Specific Dangers	Flammable liquid, will support combustion. Combustion produces toxic gases.
Flammability	Flammable.
Extinguisher Type	Use a dry chemical, alcohol resistant foam, water spray. DO NOT USE WATER JET.
Hazchem code	3Y

6. ACCIDENTAL RELEASE MEASURES

Emergency and Evacuation

Procedures Keep area well ventilated.
Remove all sources of ignition and avoid generating sparks or static discharge.
Do not let product enter drains or natural waterways.
Use personal protective equipment. See section 8.

Minor Spills Mop up spill and wash area with detergent and water.

Major Spills Contain spill. Collect product using a suitable absorbent material such as vermiculite. Shovel material into a clean, dry, labelled container and close lid tightly. Do not allow product to enter waterways.

7. HANDLING AND STORAGE

Handling Dangerous Goods Class 3. Handle accordingly.
Take precautions against static discharge if liquid is poured.
Wear suitable gloves if long or repeated exposure to the product is anticipated.

Storage Dangerous Goods Class 3. Store accordingly.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards - Australia

Exposure Standards⁽¹⁾ have been set for the following ingredients:

Ingredient	CAS No. ^(a)	TWA		STEL		Carcinogen Category	Notices
		ppm ^(b)	mg/m ^{3(c)}	ppm ^(b)	mg/m ^{3(c)}		
Ammonia ²	7664-41-7	25	17	35	24	-	-
Quartz	14808-60-7	-	0.1	-	-	-	-

Exposure Standards - New Zealand

Exposure Standards⁽³⁾ have been set for the following ingredients:

Ingredient	CAS No. ^(a)	TWA		STEL	
		ppm ^(b)	mg/m ^{3(c)}	ppm ^(b)	mg/m ^{3(c)}
Ammonia ²	7664-41-7	25	17	35	24
Quartz	14808-60-7	-	0.2 Respirable dust	-	-
Kaolin	1332-58-7	-	10 Inspirable dust 2 Respirable dust	-	-

TWA = Time Weighted Average

STEL = Short Term Exposure Limit

⁽¹⁾ Worksafe Australia Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003 1995]

⁽³⁾ Workplace Exposure Standards endorsed by the Occupational Safety and Health Service (OSH) of the Department of Labour; Revised: January 2002

^(a) CAS #, Chemical Abstracts Service Registry. A unique numbering identifier is assigned to each individual chemical.

^(b) Parts of vapour or gas per million of contaminated air by volume at 25°C and 760 torr.

^(c) Milligrams of substance per cubic metre of air.

⁽²⁾ Ammonia in solution exists as ammonium hydroxide (Cas # 1336-21-6) and may release ammonia vapours (Cas # 7664-41-7)

Engineering Controls	Ensure adequate ventilation. Maintain air concentrations below set exposure standards.
Personal Protection	When handling bulk quantities, wear suitable gloves, protective clothing and goggles. If ventilation is inadequate wear a respirator fitted with an organic vapour cartridge.
Work/Hygienic Practices	Wash thoroughly with soap and water after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Appearance	Clear, viscous
Colour	Light brown
Density (20°C)	0.975 - 1.0 g/mL
Flashpoint	38 - 42°C (solvent)
Solubility in Water	Immiscible
pH	11.0 - 11.5 at 20°C
Kinematic Viscosity	25.2 mm ² /s @ 40°C 25.2 x 10 ⁻⁶ m ² /sec

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Dangerous Reactions	Avoid strong oxidants and acids.
Conditions to Avoid	Sources of ignition.
Incompatible Materials	Avoid oxidising agents.
Decomposition Products	Incomplete combustion produces toxic gases.

11. TOXICOLOGICAL INFORMATION

Acute Effect(s) Eye	May cause irritation to the eyes.
Skin	Will cause irritation to the skin. Frequent or prolonged contact may cause defatting of skin, irritation and dermatitis.
Inhaled	Vapours may cause irritation to the upper respiratory tract.
Swallowed	Minimal toxicity. The viscosity of this preparation mitigates the risk of aspiration into the respiratory system during ingestion or vomiting.
Sensitisation	Not expected to be a skin sensitiser.

Chronic Effect(s)	The chronic toxicity of this product has not been determined.
Toxicity Information	Information is based on available component data and their concentrations in the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity	This product contains >60% white spirit which is highly volatile and will rapidly evaporate to the air if released into the environment. Based upon data for similar materials white spirit is classified as toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
-------------	--

13. DISPOSAL CONSIDERATIONS

Disposal Method	Product should be treated according to the instructions given under sections 6,7 and 8 above. Dispose of according to Local, State and Federal regulations. Contact relevant authority for details.
-----------------	--

14. TRANSPORT INFORMATION

Road Transport Regulations (ADG)
 UN number: 1300
 Proper shipping name: TURPENTINE SUBSTITUTE
 DG class: 3
 Subsidiary risk: None allocated
 Packing group: III
 Hazchem code: 3Y

Maritime Transport Regulations (IMDG)
 UN number: 1300
 Proper shipping name: TURPENTINE SUBSTITUTE
 DG class: 3
 Subsidiary risk: None allocated
 Packing group: III
 Marine Pollutant: Marine Pollutant

Air Transport Regulations (IATA)
 UN number: 1300
 Proper shipping name: TURPENTINE SUBSTITUTE
 DG class: 3
 Subsidiary risk: None allocated
 Packing group: III

15. REGULATORY INFORMATION

AUSTRALIA	
Regulatory Status	Not applicable.
Hazardous Substances Regulation	Hazardous
Risk Phrase(s)	R10 Flammable R67 Vapours may cause drowsiness and dizziness R51/53 Toxic to aquatic organisms, may cause long term effects in the aquatic environment.
Safety Phrase(s)	S2 Keep out of reach of children.

S24 Avoid contact with skin
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29 Do not empty into drains.
S61 Avoid release into the environment.
S62 If swallowed, do not induce vomiting, seek medical advice immediately and show this container or label.

SUSDP	Poisons Schedule Number: S5 (Hydrocarbons liquid, Ammonia)
NEW ZEALAND Regulatory Status	This product has been approved under HSNO covered by Cleaning Products (Flammable) Group Standard 2006 HSR002528.
Approved Handler	Not required
Tracking	Not required

16. OTHER INFORMATION

CONTACT POINT

AUSTRALIA & NEW ZEALAND:
Regulatory, Safety & Environmental Services

Within Australia	Ph: (02) 9857 2000
Outside Australia	Ph: 61-2-9857 2000

The information contained in this MSDS was compiled using the latest and most reliable information available to Reckitt Benckiser. The information is provided without any warranty, expressed or implied regarding its correctness or accuracy. Similarly no warranty expressed or implied regarding the product described herein shall be created by or inferred from any statement or omission from this MSDS nor will Reckitt Benckiser assume any liability for any loss or damage arising out of the use of this information. It is solely the responsibility of the user to determine safe conditions for use of this product and to assume liability for any loss, damage or expense whatsoever arising out of the product's improper use.

KEY/LEGEND

AICS = Australian Inventory of Chemical Substances
NOHSC = National Occupational Health and Safety Commission (Australia)
SUSDP = Standard for the Uniform Scheduling of Drugs and Poisons (Australia)
ADG = Australian Code for the Transport of Dangerous Goods by Road and Rail
IATA = International Air Transport Association
IMDG = International Maritime Organization Rules
HSNO = Hazardous Substances and New Organisms

This document is only current on the day of viewing. Printed copies are UNCONTROLLED unless they are a part of a Quality/ Technical Manual or attached to a letter referring to Purchase Order Number. END OF DOCUMENT.